



Neff - D1613W0GB White
Conventional hood, 60 cm wide
Conventional hood

- Suitable for ducted extraction and recirculation
- Switch control operation
- 3 speeds
- 1 x 40 W lights
- Glass visor
- Universal charcoal grease filter
- Ducted extraction rate according to DIN/EN 61591: max. 190 m³/h
- Suitable for ducted or re-circulated extraction
- Extraction rate freeblowing max. 210 m³/h

Optional accessories:

- Z5200X0 : Accessory
- Z5110X3 : Active carbon filter

Characteristics

Product name/family :
Color chimney :
Typology : Built-under (classic)
Approval certificates : VDE, CE
Length electrical supply cord (m) : 130.0
Required niche size for installation (HxWxD) : x
x
Height of the chimney (mm) :
Height of product, without chimney (mm) :
Dimensions of the product, with chimney (if exists) (mm) : 140 x 598 x 510
Net weight (kg) : 8.00
Type of control : mechanical
Number of speed settings : 3-stage
Maximum output air extraction (m³/h) : 190
Boost position output recirculating (m³/h) :
Maximum output recirculating air (m³/h) : 150
Boost position air extraction (m³/h) :
Number of lights (Stck) : 1
Noise level (dB) :
Diameter of air outlet (mm) : 100 / 120
Grease filter material : Not washable synthetic

Consumption and connection features

Connection Rating (W) : 125
Current (A) :
Voltage (V) : 220-240
Frequency (Hz) : 50
Plug type : GB plug
Installation typology : Under cabinet

Alternative colors available:

- D1613S0GB : Extractor hoods
- D1613N0GB : Extractor hoods
- D1613B0GB : Extractor hoods

Extractor hoods
Neff - D1613W0GB

Predecessor:
Successor:

EAN code: 4242004070740

sales programme:

Included accessories: